

Datenblatt für Artikel: BK090202--

Falonkívüli elosztó, 1 sor, 18KE, átlátszó ajtó, IP65

UV-álló, 1000V DC; anyaga ABS, 1x18KE, MA = 288 mm, SZÉ = 432 mm, MÉ = 160 mm,
1x N+PE (22x16mm²)



SCHRACK-Info

- Wall-mounted enclosures with one transparent door inclusive UV-Protection
- Lock: Pressure-operated mechanism, a small cylinder can be installed
- Cable Entry by elastic rubber membranes
- Includes PE and N terminals
- Halogen-free plastic materials
- Protection class II
- UV stability and weather resistant

- Rated voltage 400VAC, 1000VDC
- Ambient temperature: -25° to +85°C
- Material: ABS
- Degree of protection IP65
- Resistance to impact: IK07
- RAL7035 light grey

Technische Daten

Nettó szélesség (mm)	432,00
Nettó magasság (mm)	288,00
Nettó mélység (mm)	160,00
Nettó tömeg (kg)	2,54
EAN-CODE	9004840817935
Veszteségi teljesítmény (W)	-35,00
Min. környezeti hőmérséklet (°C)	-25
Max. környezeti hőmérséklet (°C)	85

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Falonkívüli elosztó, 1 sor, 18KE, átlátszó ajtó, IP65	
UV-álló, 1000V DC; anyaga ABS, 1x18KE, MA = 288 mm, SZÉ = 432 mm, MÉ = 160 mm, 1x N+PE (22x16mm ²)	BK090202
Választható tartozék	
Félcilinder zár BK09-hez, IP65	BK090097