

Datenblatt für Artikel: DTWI126040

Kommunikációs fali szekrény, IP55 beltéri, 663x600x450, 12U

19", RAL7035, üveg ajtó



SCHRACK-Info

Network wallmount 19" IP55 Indoor Cabinets are designed for industrial applications. Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application areas are semi-open areas like factories, warehouses, lean-to roof conditions, without no direct rain and environmental effects. Totally gasketed doors, IP55 performing swing handle locking with 3 point locking system and isolated cable entries provide best performance for water and dust ingress.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides the corrosion resistance.

Passive ventilation via filtered inlets.

TECHNICAL DATA

- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Height: 12U
- Width: 600mm


- Depth: 450mm
- Maximum Load: 100kg
- Door: Glass door including keyed swing lock handle with 3point locking system provides security and anti-vandal structure, also maintaining the IP55 protection
- Included are 4 pcs. 3,0 mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included
- Cabinets are delivered with: 1 set = 2pcs 19" front rails. A second pair of 19" DTWIPROFxx rails for rear mounting is available as an option. This is required for 4-point mounting of heavy equipment.




Technische Daten

Nettó szélesség (mm)	600,00
Nettó magasság (mm)	663,00
Nettó mélység (mm)	450,00
Nettó tömeg (kg)	31,50
Min. környezeti hőmérséklet (°C)	5
Max. környezeti hőmérséklet (°C)	40
Alkalmazható szekrény szélességhez (mm)	600
Magasság (mm)	663
Szín	RAL 7035 (világos szürke)
Leírás	Elosztó


méretrajz: Kommunikációs fali szekrény, IP55 beltéri, 663x600x450, 12U




Top view




Bottom view




Inside view


méretrajz: Kommunikációs falı szekrény, IP55 beltéri, 663x600x450, 12U

méretrajz: Kommunikációs faliszekrény, IP55 beltéri, 663x600x450, 12U

Front view




Side view




Rear view

méretajz: Kommunikációs falı szekrény, IP55 beltéri, 663x600x450, 12U



méretarajz: Kommunikációs faliszekrény, IP55 beltéri, 663x600x450, 12U



méretarajz: Kommunikációs faliszekrény, IP55 beltéri, 663x600x450, 12U

	A		B	
	Min	Max	Min	Max
D=450	60 mm	185 mm	260 mm	385 mm
D=600	60 mm	335 mm	260 mm	535 mm

adat táblázat: Kommunikációs faliszekrény, IP55 beltéri, 663x600x450, 12U

Typ	h [mm]	H [mm]	Gewicht Netto [kg]	Gewicht Brutto [kg]
DTWI076040	311	440	27	28
DTWI096040	400	529	30,5	31,5
DTWI126040	533	663	33,5	34,5
DTWI166040	711	841	37,2	38,2
DTWI076042	311	440	25	26
DTWI096042	400	529	28	29
DTWI126042	533	663	31	32
DTWI166042	711	841	37	38

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Kommunikációs fali szekrény, IP55 beltéri, 663x600x450, 12U 19", RAL7035, üveg ajtó	DTWI126040
Választható tartozék	
Tetőventilátor IP54, 1 ventilátor, ki-be kapcsoló, RAL7035 DTWI IP55 fali szekrényhez, szerelés a szekrényen kívülről	DTLTR5521
Tetőventilátor IP54, 2 ventilátor, ki-be kapcsoló, RAL7035 DTWI IP55 fali szekrényhez, szerelés a szekrényen kívülről	DTLTR5522
19" szerelősín készlet, 12U f. S-RACK fali szekrényhez DTWI 1 tétel = 2 db	DTWIPROF12
Kihajtható karos zár átalakító készlet S-RACK szekrényhez félcilinderhez	DTZLOCK02
Adapter félcilinder zárbetéthez DTWI szekrényhez DTZLOCK02- szükséges	DTZLOCK05
Switch 24xRJ45 10/100/1000, csendes, belső tápegység Fémváz, 19"	QLGSW2457
19" dugaszolóaljzatsáv, 9 dugaszolóaljzattal, 1U	IU070114
19" dugaljzatsáv 7 dugaljzat+túlfeszültség-védelem 1.25U 2m-es csatlakozó vezeték, RAL7035	IU070113
19" PDU, 9x Schuko, switch, 1U, 2m-cable, Black, ALU ALU Profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U 2m-cable, Black, ALU	Q7070113-A