

Datenblatt für Artikel: DTWI206060

Kommunikációs fali szekrény, IP55 beltéri, 1018x600x600, 20U

19", RAL7035, üveg ajtó



SCHRACK-Info

Network wallmount 19" IP55 Indoor Cabinets are designed for industrial applications. Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application areas are semi-open areas like factories, warehouses, lean-to roof conditions, without no direct rain and environmental effects. Totally gasketed doors, IP55 performing swing handle locking with 3 point locking system and isolated cable entries provide best performance for water and dust ingress.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides the corrosion resistance.

Passive ventilation via filtered inlets.

TECHNICAL DATA


- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Height: 20U
- Width: 600mm

- Depth: 600mm
- Maximum Load: 100kg
- Door: Glass door including keyed swing lock handle with 3point locking system provides security and anti-vandal structure, also maintaining the IP55 protection
- Included are 4 pcs. 3,0 mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included
- Cabinets are delivered with: 1 set = 2pcs 19" front rails. A second pair of 19" DTWIPROFxx rails for rear mounting is available as an option. This is required for 4-point mounting of heavy equipment.


Technische Daten

Nettó szélesség (mm)	600,00
Nettó magasság (mm)	1.018,00
Nettó mélység (mm)	600,00
Nettó tömeg (kg)	50,00
Min. környezeti hőmérséklet (°C)	5
Max. környezeti hőmérséklet (°C)	40
Alkalmazható szekrény szélességhez (mm)	600
Magasság (mm)	1018
Szín	RAL 7035 (világos szürke)
Leírás	Elosztó


méretrajz: Kommunikációs fali szekrény, IP55 beltéri, 1018x600x600, 20U




Top view




Bottom view




Inside view




Front view




Side view




Rear view



Top inside view



Front door opening angle




3 point locking system

	A		B	
	Min	Max	Min	Max
D=450	60 mm	185 mm	260 mm	385 mm
D=600	60 mm	335 mm	260 mm	535 mm

	D
7U	298 mm
9U	387 mm
12U	520 mm
16U	698 mm
20U	876 mm

méretarajz: Kommunikációs faliszekrény, IP55 beltéri, 1018x600x600, 20U



Artikeltabelle

BEZEICHNUNG	BEST.NR.
Kommunikációs faliszekrény, IP55 beltéri, 1018x600x600, 20U	DTWI206060
19", RAL7035, üvegajtó	
Választható tartozék	
Tetőventilátor IP54, 1 ventilátor, ki-be kapcsoló, RAL7035	DTLTR5521
DTWI IP55 faliszekrényhez, szerelés a szekrényen kívülről	

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Választható tartozék	
Tetőventilátor IP54, 2 ventilátor, ki-be kapcsoló, RAL7035	DTLTR5522
DTWI IP55 fali szekrényhez, szerelés a szekrényen kívülről	
19" szerelősín készlet, 16U f. S-RACK fali szekrényhez DTWI	DTWI PROF16
1 tétel = 2 db	
Kihajtható karos zár átalakító készlet S-RACK szekrényhez	DTZLOCK02
félcylinderhez	
Adapter félcylinder zárbetétéhez DTWI szekrényhez	DTZLOCK05
DTZLOCK02- szükséges	
Switch 24xRJ45 10/100/1000, csendes, belső tápegység	QLGSW2457
Fémváz, 19"	
19" dugaszolóaljzatsáv, 9 dugaszolóaljzattal, 1U	IU070114
19" dugaljzatsáv 7 dugaljzat+túlfeszültség-védelem 1.25U	IU070113
2m-es csatlakozó vezeték, RAL7035	
19" PDU, 9x Schuko, switch, 1U, 2m-cable, Black, ALU	Q7070114-A
ALU Profil	
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U	Q7070113-A
2m-cable, Black, ALU	