


Datenblatt für Artikel: HLP23LT03F

Opt. patchkábel duplex LC/UPC - ST/UPC, 50/125µm OM3, LSOH

Vízkek, 3m



SCHRACK-Info

Multimode patch cords are mainly used for short-distance communication with high transmission rates, for example within a building or on a campus. The multimode patch cords are equipped with an LSOH-jacket. These comply with IEC or EIA-TIA standards. These multimode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- LC/UPC - ST/UPC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Multimode cabled fiber conforms to ITU-T G.651.1, IEC 60793-2-10
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks


- ATM, SONET and WDM



Technische Daten

Szabvány	IEC 61300-3-4 / IEC 61300-3-6
Csatlakozó szabvány	IEC 61754
Csatlakozó kombináció	LC/ST
Patchkábel hossz (m)	3
Szál	50/125 μ OM3 multimódusú
Kábel köpeny	LS0H
Szín	víz
Jellemző bemeneti veszteség (dB)	$\leq 0,25$
Jellemző visszaverődési veszteség (dB)	≥ 30
Min. környezeti hőmérséklet (°C)	-20
Max. környezeti hőmérséklet (°C)	60
Nettó szélesség (mm)	210,00
Nettó magasság (mm)	320,00
Nettó tömeg (kg)	0,14

méretrajz: Opt. patchkábel duplex LC/UPC - ST/UPC, 50/125 μ m OM3, LS0H



BEZEICHNUNG

BEST.NR.

Opt. patchkábel duplex LC/UPC - ST/UPC, 50/125µm OM3, LSOH
Vízkek, 3m

HLP23LT03F