

Datenblatt für Artikel: HSATWT50S-

SAT Mast Bracket Set 50 cm, mast tubes D=38-60 mm, steel

hot-galvanized, two-part



SCHRACK-Info

Hot-dip galvanized steel wall bracket, 2-part, for the securely attaching a mast tube with a diameter of Ø 38 to 60mm to the wall. Wall distance: 150mm, adjustable by 10cm. Mast tube not included.

TECHNICAL DATA

- Material: Quality steel
- Struts : Flat profile 30 x 5mm
- Surface: hot-dip galvanizing approx. 80
- Wall distance: 500mm, adjustable up to 10cm
- twist-proof: with 2x twist-proof claws
- consisting of: 1x bipod and 1x tripod holder
- suitable for mast tubes : Ø 38 to 60mm

Technische Daten

Nettó hosszúság (mm)	520,00
Nettó szélesség (mm)	560,00
Nettó magasság (mm)	50,00
Nettó tömeg (kg)	3,90
Min. környezeti hőmérséklet (°C)	-40
Max. környezeti hőmérséklet (°C)	60

Artikeltabelle

BEZEICHNUNG	BEST.NR.
SAT Mast Bracket Set 50 cm, mast tubes D=38-60 mm, steel hot-galvanized, two-part	HSATWT50S
Választható tartozék	
SAT árbóc, hossz=2000mm, átmérő=50mm, 1,5mm tűzihorg. acél	HSATMM20S
SAT árbóc, hossz=2000mm, átmérő=60mm, 2,0mm tűzihorg. acél	HSATMM20S6
SAT árbóc, hossz=3000mm, átmérő=50mm, 2,0mm tűzihorg. acél	HSATMM30S
SAT Mast, Length=3000mm, DM=60mm, 2.0mm Steel hot-galvanized	HSATMM30S6