




Datenblatt für Artikel: HSELS2400W

FTTx üres kültéri opt. szerelődoboz 24 szálas, fali, IP54

Szé200xMax235Mé67, RAL7035 világosszürke, tartalmaz három moduláris adaptert 12xLC-Dx, SC-Sx, E-2000®-Sx vagy 9x SC-Dx / 6x LC-QD csavarokkal, 12x SC-Dx or LC-QD kuplung részére csavarokkal.



SCHRACK-Info

Application

- Easy to mount splicebox for the indoor or outdoor construction of fibre optic distribution with the possibility of mounting a profile half cylinder
- Suitable for up to 24 optical fibres

Technical Data

- Structured ASA (Acrylester-Styrol-Acrylnitril), extremely durable plastic, impact-resistant and weatherproof
- Cover locking by locking hooks with the option of sealing
- Splice cassette for easy installation and maintenance with maximum protection of the fibres with cross-out option and overlength tray
- Prepared for installation of profile half cylinder
- Strain relief for cables and patch cords
- Mounting option and fixation for gas - / water blockers available
- Patch cable outlet with flexible lamellar seal
- Modular adapter plate with cut-outs for fibre optic adapters included
 - Adapter plate 1: for up to 12x LC-Dx, SC-Sx or E-2000® -Sx
 - Adapter plate 2: for up to 9x SC-Dx or 6x LC-Quad
 - Adapter plate 3: for up to 12x SC-Dx, 6x LC-Quad without flange
- Equipped with 1x set (30 pcs) heat shrink splice protector for crimp splice holder
- Mounting option for 2x PCL splitter (40x4mm)
- Cable entry with 2x M20, 2x M25 cable gland possible
- Color: RAL7035 Light grey
- Protection class as per IEC 60529: IP54

Climate area

- During transport: -25 °C bis +70 °C
- During installation: -5 °C bis +50 °C
- During operation: -5 °C bis +70 °C

Mechanical Data

- Material: ASA, halogenfrei und schlagfest
- Dimensions:
 - Width: 200mm
 - Height: 235mm
 - Depth: 67mm
- Weight: 1,04kg

Accessories

- HSELSZSH12: FO shrink splice protector 45mm for FTTx Spliceboxes HSELS1200W / HSELS2400W
- DV900333--: Half cylinder lock keyed EK 333 including 1 key. (Countersunk screw M5x12mm is required)
- HSELSZMK01: Pole attachment for splicebox HSELSxx00W, diameter 60-215mm
- HSELSZMK02: Pole attachment for splicebox HSELSxx00W, diameter 60-325mm

Technische Daten

Nettó szélesség (mm)	200,00
----------------------	--------

Technische Daten - Fortsetzung

Nettó magasság (mm)	235,00
Nettó mélység (mm)	67,00
Nettó tömeg (kg)	1,04
Min. környezeti hőmérséklet (°C)	-5
Max. környezeti hőmérséklet (°C)	70

Artikeltabelle

BEZEICHNUNG	BEST.NR.
FTTx üres kültéri opt. szerelődoboz 24 szálal, fali, IP54	
Szé200xMax235Mé67, RAL7035 világosszürke, tartalmaz három moduláris adaptert 12xLC-Dx, SC-Sx, E-2000®-Sx vagy 9x SC-Dx / 6x LC-QD csavarokkal, 12x SC-Dx or LC-QD kuplung részére csavarokkal.	HSELS2400W
Választható tartozék	
Oszlop rögzítő konzol HSELSxx00W kötődobozhoz átm. 60-215mm	
Rozsdamentes acél, alkalmas lámpaoszlopokra, zászló tartó oszlopokra, szerelési segédanyagokat tartalmazza	HSELSZMK01
Oszlop rögzítő konzol HSELSxx00W kötődobozhoz átm. 60-325mm	
Rozsdamentes acél, alkalmas lámpaoszlopokra, zászló tartó oszlopokra, szerelési segédanyagokat tartalmazza	HSELSZMK02
Optikai hegesztésvédő zsugorcső, 45mm, 100 db	
FTTx Kültéri kötődobozhoz: HSELS1200W / HSELS2400W	HSELSZSH12
EK 333 kulcsos félcilinder zárbetét, 1 db kulccsal	
Tartalmaz 1 db M5×16 mm-es V2A sülyesztett fejű csavart.	DV900333S