

Datenblatt für Artikel: HSELS245LP

Optikai rendező 24szálas LC 50/ 125µm OM2, kihúzható, 19"1U

acc. to IEC 61753-1, RAL7035, sliding, Pigtails included, CLASSIC



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Technische Daten

Nettó szélesség (mm)	480,00
Nettó magasság (mm)	44,00
Nettó mélység (mm)	242,00
Nettó tömeg (kg)	2,53
Szín	RAL 7035 (világos szürke)
Min. környezeti hőmérséklet (°C)	-10
Max. környezeti hőmérséklet (°C)	70
Jellemző bemeneti veszteség (dB)	< 0,2
Jellemző visszaverődési veszteség (dB)	> 35
Szál	50/125µ OM2 multimódusú
Szálszám	24

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optikai rendező 24szálas LC 50/125µm OM2, kihúzható, 19"1U acc. to IEC 61753-1, RAL7035, sliding, Pigtailed included, CLASSIC	HSELS245LP
Választható tartozék	
FO optikai kábel kötés védelem, 60mm	HELSP00011
FO optikai kábel kötés védelem, 40mm	HELSP00010
Opt. patchkábel duplex LC/LC,50/125µm OM2,LSOH-3,narancs 2m	HLP25LL02F
Opt. patchkábel duplex LC/LC,50/125µm OM2,LSOH-3,narancs 5m	HLP25LL05F
Opt. patchkábel duplex LC/SC,50/125µm OM2,LSOH-3,narancs 2m	HLP25LC02F
Opt. patchkábel duplex LC/SC,50/125µm OM2,LSOH-3,narancs 5m	HLP25LC05F
Opt. patchkábel duplex LC/ST,50/125µm OM2,LSOH-3,narancs 2m	HLP25LT02F
Opt. patchkábel duplex LC/ST,50/125µm OM2,LSOH-3,narancs 5m	HLP25LT05F