

Datenblatt für Artikel: MGC52008--

Áramváltó 75/5A 21 mm átmérő, class 1

Primer áram 75A, Burden Class 1 (1.5VA)



Technische Daten

Védettségi fokozat	IP20
Burden	Class 1 (1.5VA)
Note	Due to dangerous overvoltage and overheating, the Current Transformer is not allowed to be operated with open secondary Side. (EN 60044-1 /A2) As soon as the Measurement Device, the Energy Counter or the Net Analyzer is disconnected, the secondary Side has to be shortcuted!
Intended use	for cables up to diameter 21 mm
Szabvány	EN 61869-2
Kivágás mérete (mm)	21
Insulation requirements	
Max. Operating voltage Um	0.72kV r.m.s.
Isolation test voltage	3 kV R.M.S. 50 Hz/ 1 min
Isolation	Class B (EN/IEC 61869-1, 61869-2)
Specifications	
Rated current primary side Ipr (A)	75
Rated frequency (Hz)	50-60Hz
Short-time current Ith	< 60Ipr

Technische Daten - Fortsetzung

Thermal rated continuous current according to EN60044-1

Rated dynamic current I_{dyn}	2.5Ith
Rated current secondary side I_{sr}	5A
Tightening torque (Nm)	2
Housing material	Polycarbonate, self-extinguishing





Accuracy classes

Reference temperature (°C)	23°C ±1°C
Load current error	For class 1 and 20% I_n : ±1.5% For class 1 and 5% I_n : ±3%. For class 1 and 100% I_n : ±1%. For class 1 and 120% I_n : ±1%

Working conditions

Hőmérséklet tartomány, szállítás (°C)	-25 to +60
Hőmérséklet tartomány, üzemi (°C)	-5 to +40

Maßbild MGC52008--



BEZEICHNUNG	BEST.NR.
Áramváltó 75/5A 21mm átmérő, class 1 Primer áram 75A, Burden Class 1 (1.5VA)	MGC52008