

Datenblatt für Artikel: Q7171199--

# HDMI hosszabító HDMI-A - Cat.5e/6 >30m (2xRJ45), HDMI 1.3b



## SCHRACK-Info

The Q7171199-- uses two pieces of CAT 5e/6 HIGH SPEED cables to extend the HDTV display up to 60 meters for 1080P. It not only breaks the limitation of the HDMI cable transmission length, but also CAT 5e/6 has more flexibility and convenience in cable construction.

### Specification

- Compliance with HDMI High Speed specification
- 2 HDMI Adapters for CAT 5/6 patch cable
- Automatic device configuration
- Supports 1080p with Cat 6 patch cable up to 30m
- HDTV: 480i/576i/480p/576p/720p/1080i/1080p
- Supports Dolby Digital, DTS Digital, DTS HD, Dolby True HD
- Bandwidth: 2.25 Gbit/s at 225 MHz per channel (8.16 Gbit/s total)
- Supports HDCP pass-through, LPCM
- Supports 8bit per channel (24bit all channel) deep color

### Package contents

- 1 x Main unit NO. 1 Transmitter
- 1 x Main unit NO. 2 Receiver
- 1 x External Power Supply
- 1 x User Manual

## Packaging Information

- Packing Dimension: 190×145×60 mm
- Packing Weight: 0.47kg
- Carton Dimension: 505×340×235mm
- Carton Quantity: 15pcs
- Carton Weight: 7.8kg

## Technische Daten

|                                  |               |
|----------------------------------|---------------|
| Nettó hosszúság (mm)             | 81,00         |
| Nettó szélesség (mm)             | 45,00         |
| Nettó magasság (mm)              | 25,00         |
| Nettó tömeg (kg)                 | 0,36          |
| EAN-CODE                         | 4260113565742 |
| Min. környezeti hőmérséklet (°C) | 5             |
| Max. környezeti hőmérséklet (°C) | 45            |
| Termék                           | egyebek       |

## adat táblázat: HDMI hosszabító HDMI-A - Cat.5e/6 >30m (2xRJ45), HDMI 1.3b

| Signal Inputs/Output      |                                |
|---------------------------|--------------------------------|
| Input Video Signal        | 0.5 - 1.0 volts p-p            |
| Input DDC Signal          | 5 volts p-p (TTL)              |
| Maximum Single Link Range | 1920x1080p                     |
| Output Video              | HDMI High Speed                |
| Operating Frequency       |                                |
| Vertical Frequency Range  | 50/60Hz                        |
| Video Amplifier Bandwidth | 1.65Gbps/165MHz                |
| Transmission distance     |                                |
| CAT-6 cable               | 30M for 1080p                  |
| Resolutions (HDTV)        |                                |
| Interlaced (50&60Hz)      | 480i, 576i, 1080i              |
| Progressive (50&60Hz)     | 480p, 576p, 720p, 1080p        |
| Enviromental              |                                |
| Operating Temperature     | 0-70°C                         |
| Operating Humidity        | 10 to 85% RH (no condensation) |
| Storage Temperature       | -10 to 80°C                    |
| Storage Humidity          | 5 to 95% RH (no condensation)  |
| Power Requirement         |                                |
| External Power Supply     | 5V DC, 2A                      |
| Power consumption (Max)   | 5W                             |

BEZEICHNUNG

BEST.NR.

HDMI hosszabító HDMI-A - Cat.5e/6 >30m (2xRJ45),HDMI 1.3b

Q7171199